

Produto | Product

Sistema termostático embutido de banheira com chuveiro de parede Ø250 mm em Inox, kit de chuveiro mão Elo e válvula com bica de enchimento para banheira – VenusQ | *Thermostatic concealed bath-shower set with Inox shower head Ø250 mm, Elo handshower set and bath filler with waste and overflow – VenusQ*

187 413 1XX

IMAGEM* | IMAGE*



ESPECIFICAÇÕES | SPECIFICATIONS

- Sistema termostático embutido de banheira com chuveiro de parede Ø250 mm em Inox, kit de chuveiro mão Elo e válvula com bica de enchimento para banheira – VenusQ;
- Cartucho termostático;
- Tecnologia para menor consumo de água BRUMA AirEcoDrop®;
- Sistema anticalcário BRUMA ConfortClean®;
- Chuveiro de mão – Elo e chuveiro com redutor de caudal 6 l/min;
- Limitador de temperatura a 38°C;
- Com elemento encastrável INT 630 2NO.

- Thermostatic concealed bath-shower set with Inox shower head Ø250 mm, Elo handshower set and bath filler with waste and overflow – VenusQ;
- Thermostatic compact cartridge;
- Water-saving technology BRUMA AirEcoDrop®;
- Anti-limescale system BRUMA ConfortClean®;
- Hand shower – Elo with flow reducer 6 l/min;
- Safety stop limits the temperature range to 38 °C;
- With concealed body INT 630 2NO.



DESENHO DIMENSIONAL | DIMENSIONAL DRAWING




DIAGRAMA CAUDAL | FLOW DIAGRAM

Caudais a 3 bar:

- Chuveiro de mão: 6,0 l/min.
- Chuveiro de parede: 6,0 l/min.
- Válvula com bica de enchimento: 10,0 l/min.

Flow rate at 3 bar:

- Handshower: 6,0 l/min.
- Shower head: 6,0 l/min.
- Bath filler with waste and overflow: 10,0 l/min.

EFICIÊNCIA HÍDRICA | WATER LABEL **A +**

INSTRUÇÕES DE MANUTENÇÃO | MAINTENANCE INSTRUCTIONS




Product


Elemento encastrável | *Concealed body*

INT 630 2NO

IMAGEM* | *IMAGE**



DESENHO DIMENSIONAL | *DIMENSIONAL DRAWING*



ESPECIFICAÇÕES | *SPECIFICATIONS*

- Elemento encastrável;
- Cartucho termostático com elemento sensível Vernet;
- Cartucho inversor de discos cerâmicos;
- Inclui parafusos e buchas para fixação.

- *Concealed body;*
- *Thermostatic cartridge with Vernet sensitive element;*
- *diverter cartridge with ceramic discs;*
- *Screws and plugs included.*


DIAGRAMA CAUDAL | *FLOW DIAGRAM*

Caudais a 3 bar:

- Saída 1 (sem restrição): 26,30 l/min
- Saída 2 (sem restrição): 24,70 l/min
- Saída 3 (sem restrição): 24,70 l/min



Flow rate at 3 bar:

- Outlet 1 (without restrictor): 26,30 l/min
- Outlet 2 (without restrictor): 24,70 l/min
- Outlet 3 (without restrictor): 24,70 l/min



Inversor
Diverter

Termostático
Thermostatic



Fechado | *OFF*